



**OUTDOOR SINGLE
PANEL KIOSK**

OUTDOOR SINGLE PANEL KIOSK

WA-O430-FSS/ WA-O490-FSS/ WA-O550-FSS/
WA-O650-FSS/ WA-O750-FSS

DESCRIPTION

The Single Panel Kiosk is a robust and versatile outdoor display solution designed to deliver clear, impactful information in various environments. Featuring a sleek, single-panel design, this kiosk is built to withstand outdoor conditions while providing high-resolution visuals. Its weather-resistant construction ensures reliable performance in rain, wind, and sunlight, making it ideal for public spaces, information stands, and advertising. With a bright display that enhances visibility even in direct sunlight, the Single Panel Kiosk offers a durable and stylish way to engage and inform your audience, combining functionality with modern aesthetics for effective outdoor communication. Available in sizes of 43, 49, 55, 65, and 75 inches, it features display areas ranging from 530 x 941 mm to 928 x 1650 mm.

The high-resolution 1080 x 1920 screen ensures crisp, vibrant visuals, while brightness levels of 2000-2500 cd/m² guarantee excellent visibility even in direct sunlight. Ideal for public spaces, information stands, and advertising, the Single Panel Kiosk provides a stylish and effective way to engage and inform your audience.



DISPLAY PARAMETERS

Size	43 Inch	49 Inch	55 Inch	65 Inch	75 Inch
Model	WA-O430-FSS	WA-O490-FSS	WA-O550-FSS	WA-O650-FSS	WA-O750-FSS
Product Name	43 Inch Outdoor Single Panel Kiosk Display	49 Inch Outdoor Single Panel Kiosk Display	55 Inch Outdoor Single Panel Kiosk Display	65 Inch Outdoor Single Panel Kiosk Display	75 Inch Outdoor Single Panel Kiosk Display
Display Area	530*941mm	604*1074mm	680*1209mm	803*1428mm	928*1650mm
Proportion	9:16	9:16	9:16	9:16	9:16
Resolution	1080*1920	1080*1920	1080*1920	1080*1920	1080*1920
Brightness	2000-2500cd/m ²	2000-2500cd/m ²	2000-2500cd/m ²	2000-2500cd/m ²	2000-2500cd/m ²
Contrast Ratio	4000:1	4000:1	4000:1	4000:1	4000:1
Viewing Angle	178° (Horizontal/Vertical)	178° (Horizontal/Vertical)	178° (Horizontal/Vertical)	178° (Horizontal/Vertical)	178° (Horizontal/Vertical)

SYSTEM CONFIGURATION

Operation System	Android 11	Android 11	Android 11	Android 11	Android 11
RAM+ROM	2+32G	2+32G	2+32G	2+32G	2+32G
CPU	RK3568, Quad-core, The main frequency is up to 2.0GHz	RK3568, Quad-core, The main frequency is up to 2.0GHz	RK3568, Quad-core, The main frequency is up to 2.0GHz	RK3568, Quad-core, The main frequency is up to 2.0GHz	RK3568, Quad-core, The main frequency is up to 2.0GHz

EXTERIOR

Protection Level	IP65	IP65	IP65	IP65	IP65
Protective Glass	Toughened glass	Toughened glass	Toughened glass	Toughened glass	Toughened glass
Physical Dimension	1980*737*148mm		2200*960*130mm		
Weight	83KG		130KG		
Installation Method	Floor Standing	Floor Standing	Floor Standing	Floor Standing	Floor Standing

WORKING ENVIRONMENT

Brightness Control	Automatic photosensitive system	Automatic photosensitive system	Automatic photosensitive system	Automatic photosensitive system	Automatic photosensitive system
Temperature Control	Smart fan, automatic temperature sensing	Smart fan, automatic temperature sensing	Smart fan, automatic temperature sensing	Smart fan, automatic temperature sensing	Smart fan, automatic temperature sensing
Working Temperature	- 30°C to +50 °C	- 30°C to +50 °C	- 30°C to +50 °C	- 30°C to +50 °C	- 30°C to +50 °C
Working Humidity	5% to 90%	5% to 90%	5% to 90%	5% to 90%	5% to 90%
Input Voltage	AC 100-240V	AC 100-240V	AC 100-240V	AC 100-240V	AC 100-240V
Power	300W		400W		

APPLICATION



FINANCE



EDUCATION



RETAIL



PROPERTY
MANAGEMENT



RESIDENCIAL



HEALTH CARE



GOVERNMENT



PUBLIC FACILITIES



ENERGY



ENTERPRISE